



## TECHNICAL DATA SHEET

# Falzol Fleetkleen

**Applications:** Falzol Fleetkleen is intended primarily as a medium to high foam passenger vehicle cleaner and protector. It can be used on most surfaces including:

- Paintwork •Glass and Trim
- Components •Stainless Steel etc.

### EFFECTIVE - FALZOL FLEETKLEEN

- Removes Road Film
- Oil
- Diesel and other soilings

### SPECIAL FORMULATION - FALZOL FLEETKLEEN

- Helps prevent machine sealing in hard water areas
- Is biodegradable
- Non caustic based
- Gentle on surfaces

### DIRECTIONS:

#### Vehicle Cleaning

For use through power washers hot and cold or steam cleaners use as follows:

- (a) Wet vehicle exterior or section to be cleaned, removing any heavy dirt.
- (b) Apply Falzol Fleetkleen from bottom upwards where practical.
- (c) Allow retention time 1 - 2 minutes
- (d) Rinse thoroughly from top to bottom.

#### NOTE:

**DO NOT** allow Falzol Fleetkleen to dry on painted surfaces  
Dilute Falzol Fleetkleen before use if sponges or brushes are used.

**DILUTIONS:** Vehicle Cleaning 1% - 2.5%

Consult material safety data sheet before use:



## TECHNICAL DATA SHEET

# Falzol Fleetkleen

**Applications:** Falzol Fleetkleen is intended primarily as a medium to high foam passenger vehicle cleaner and protector. It can be used on most surfaces including:

- Paintwork •Glass and Trim
- Components •Stainless Steel etc.

### EFFECTIVE - FALZOL FLEETKLEEN

- Removes Road Film
- Oil
- Diesel and other soilings

### SPECIAL FORMULATION - FALZOL FLEETKLEEN

- Helps prevent machine sealing in hard water areas
- Is biodegradable
- Non caustic based
- Gentle on surfaces

### DIRECTIONS:

#### Vehicle Cleaning

For use through power washers hot and cold or steam cleaners use as follows:

- (a) Wet vehicle exterior or section to be cleaned, removing any heavy dirt.
- (b) Apply Falzol Fleetkleen from bottom upwards where practical.
- (c) Allow retention time 1 - 2 minutes
- (d) Rinse thoroughly from top to bottom.

#### NOTE:

**DO NOT** allow Falzol Fleetkleen to dry on painted surfaces  
Dilute Falzol Fleetkleen before use if sponges or brushes are used.

**DILUTIONS:** Vehicle Cleaning 1% - 2.5%

Consult material safety data sheet before use:



## TECHNICAL DATA SHEET

# Falzol Fleetkleen

**Applications:** Falzol Fleetkleen is intended primarily as a medium to high foam passenger vehicle cleaner and protector. It can be used on most surfaces including:

- Paintwork •Glass and Trim
- Components •Stainless Steel etc.

### EFFECTIVE - FALZOL FLEETKLEEN

- Removes Road Film
- Oil
- Diesel and other soilings

### SPECIAL FORMULATION - FALZOL FLEETKLEEN

- Helps prevent machine sealing in hard water areas
- Is biodegradable
- Non caustic based
- Gentle on surfaces

### DIRECTIONS:

#### Vehicle Cleaning

For use through power washers hot and cold or steam cleaners use as follows:

- (a) Wet vehicle exterior or section to be cleaned, removing any heavy dirt.
- (b) Apply Falzol Fleetkleen from bottom upwards where practical.
- (c) Allow retention time 1 - 2 minutes
- (d) Rinse thoroughly from top to bottom.

#### NOTE:

**DO NOT** allow Falzol Fleetkleen to dry on painted surfaces  
Dilute Falzol Fleetkleen before use if sponges or brushes are used.

**DILUTIONS:** Vehicle Cleaning 1% - 2.5%

Consult material safety data sheet before use:





## TECHNICAL DATA SHEET

# Falzol Fleetkleen Trojan

### Applications

Falzol Fleetkleen Trojan is a high-performance, high foam vehicle cleaner and degreaser for the ultimate result. Can be used on all types of vehicles - passenger, commercial etc.,

•Bodywork •Paintwork •Glass and Trim •Stainless Steel •Engines •Components

### Effective - Falzol Fleetkleen Trojan

- Removes Road Film
- Oil
- Diesel and other deposits
- Leaves surfaces sparkling
- Breaks Magnetic Bond of Road Film

### Special Formulation

- Helps Prevent Machine Scaling
- Biodegradable
- Gentle on Surfaces
- Does not contain Sodium Hydroxide
- Ideal for Pre-Dilution

### Directions

#### Vehicle Cleaning

- (a) For use through power washers hot/cold or steam.  
Cleaners use as follows:

- (a) Wet Vehicle exterior or section to be cleaned, removing any heavy dirt.
- (b) Apply Falzol Fleetkleen Trojan from bottom upwards where practical
- (c) Allow retention time 1 - 2 minutes
- (d) Rinse thoroughly top to bottom.

NOTE: Do not allow Falzol Fleetkleen Trojan to dry on painted surfaces  
Dilute Falzol Fleetkleen Trojan before use if sponges or brushes are used.

### Chassis and Engine Degreasing

Use as above at higher concentration

### Dilutions

Vehicle Cleaning 1% - 2.5%  
Degreasing 2% - 5%

Consult Material Safety Data Sheet before use.